

REITNOUER CK



Reitnouer introduces the new CK trailer line, with the same legendary Reitnouer bloodlines of quality, craftsmanship and innovation that have made Reitnouer the flatbed and drop deck trailers of choice in North America. Learn more at reitnouer-trailers.com.

- 1,000 to 1,800 lbs. lighter than comparably-equipped composite/combo trailers for more payload capacity
- Design eliminates rust and corrosion issues
- Two times the trailer lifespan over steel/aluminum combination trailers
- Backed by the best warranty in the trailer industry
- Perfect for fleets and owner-operators alike — comparably priced with standard combo trailers

See your authorized Reitnouer Dealer or visit [Reitnouer-trailers.com](http://reitnouer-trailers.com)



CK logo side placards, available in either black or red backing



Precision pre-drilled holes to easily add toolboxes between axle spread and dunnage racks on the driver's side and curb side, complete with bolts and nuts fillers.



Hendrickson Intraax® 23K/25K suspension; All steel parts finished with Corsol® WB Corrosion Protection.



Michelin PX-Line tires with 10-hole hub Pilot 22.5 or 24.5 wheels; 4 aluminum outside/4 Corsol® treated steel "silver" inside; or 8 aluminum



10 sliding double "L" winches and full-length tie bar



Peterson clear LED lights and turn signals, hard-wired, modular wiring harness with triple-sealed connections.



STANDARD SPECIFICATIONS: Reitnouer CK80, CK90 and CK100

CK-80:	80,000 lbs. GVWR*; Available in 48' and 53' x 102"; Hendrickson Intraax® 23K suspension
CK-90:	90,000 lbs. GVWR* Available in 48' and 53' x 102"; Hendrickson Intraax® 23K suspension
CK-100:	100,000 lbs. GVWR*; Available in 48' and 53' x 102"; Hendrickson Intraax® 25K suspension
Main Rail:	Two-piece extruded and bolted; 3.5" camber; 26" deep in center; 6061 T6
Cross members:	One-piece 5" double reinforced modified "C" channel on 12", 15" or 18" centers (model dependent); bolted; 6061 T6
Deck/Floor:	1-3/8" aluminum, heavy duty safety tread, interlocked, with three wood nailers; standard 45° angle front corners; full-length winch track on driver's side; 10 sliding double "L" winches on driver's side
Side Rail Assembly:	1-5/8" x 3-1/2" pockets on 2' centers with double spools between pockets, 3/8" x 2-1/2" deep rub rail; DOT tape; full-length tie bar on curb side
Outriggers:	Three-piece floating
King Pin:	24"- 36" kingpin; all steel parts finished with Corsol® WB Corrosion Protection
Coil Package:	Mini-coil package included; 6 intermediates between main beams
Axles:	5" Round; P-Spindle Ends; Wheel-end bearings; 10' 2" axle spread; automatic dump valve on all axles
Brakes:	16-1/2" x 7" extended service brakes, quick change with parking brakes; Cast drums with steel hubs
Suspension:	Hendrickson Intraax® 23K (CK80, CK90) or 25K (CK100); Available in black or red
Landing Gear:	Jost AX140 Alumilight landing legs with aluminum support brackets
Upper Coupler:	1/4" hi-tensile steel; all steel parts finished with Corsol® WB Corrosion Protection
Tires:	Michelin PX-Line; 275/80R 22.5 or 275/80R 24.5
Wheels:	10-hole hub Pilot 22.5 or 24.5; 4 aluminum outside/4 Corsol® treated steel "silver" inside; or 8 aluminum
Electrical/Lights:	7-wire main and 4-wire auxiliary plugs on front; Peterson clear LED lights, hard-wired, modular wiring harness with triple-sealed connections; 5 side lights per side; 3 stop/turn/tail per side
Bumpers:	New CK bumper with logo and mudflaps; 6 rubber dock bumpers; extruded rear corners
Bolts:	316 Stainless Steel
Finish:	Natural aluminum; all steel parts finished with Corsol® WB Corrosion Protection; New CK logo side placards, available in either black or red backing
Options:	Most popular options are available as dealer- or customer-installed options; precision pre-drilled holes to easily add toolboxes between axle spread and dunnage racks on the driver's side and curb side, complete with bolts and nuts fillers; designed to quickly and easily add bolt-on rope hooks and snow chain hangers
Warranty:	5-year standard Reitnouer Trailer Warranty

*GVWR = Gross Vehicle Weight Rating